

## AF300B Confined Space Ventilation Fan



The AF300B is a 305mm outside diameter CE marked 110 Volt electric fan. Robustly constructed the AF300B had been designed to withstand the rigours of the plant hire and construction industries.

Featuring an innovative curved handle, the AF300B can be comfortably carried by two people. This handle protects an isolator, which is connected via a 5m cable to a plug. Plastic coated finger guards, conforming to BS5304:1998, ensure the impeller cannot be reached.

The AF300B is available with a range of accessories including wire reinforced anti-static ducting, layflat ducting and outlet manifolds.



Capacity Free Air	Motor	Voltage	Current	Size	Weight	Fan Diameter	Duct Diameter
4500m3/hr	0.75kW 2800 rpm IP54	110V , 1PH 50Hz	11amps, 110V	L 440mm W 305mm H 550mm	28 Kg	292mm	305mm



### Accessories

- F2089 Wire reinforced antistatic ducting, 300mm diameter x 8m long, complete with Windlas couplings
- F2090 Layflat antistatic ducting 300mm diameter x 5m long, complete with Windlas couplings

VENTSAFE MANIFOLD					
	Length	Width	Height	Duct	Weight
Carrying Position	534 mm	457mm	419mm	305mm	8kg
	Working Position		597mm		

Also available: 110v Zone One & Air Driven Fans